




Linear strips

ROUND EDGE system


 **CBI**
EUROPE
HI-TECH INTERIORS

ROUND EDGE LINEAR STRIPS SYSTEM



STRIP DOGA

L 9000 mm max




prepainted aluminium
alluminio preverniciato
thk sp. 0.5 - 0.6 - 0.7 - 0.8 mm

prepainted galvanized steel
acciaio zincato preverniciato
thk sp. 0.4 - 0.5 - 0.6 mm

MAIN RUNNER PROFILO PORTANTE

L 3600/4000/4050 mm



galvanized steel
acciaio zincato
thk sp. 0.6 mm

colour colore
brown · galvanized
testa di moro · zincato

1




















strip
doga
length lunghezza
9000 mm max












2

carrier
profilo portante

3

adjustable suspension
sospensione regolabile

STRIPS / OPEN JOINT DOGHE / SCURETTO APERTO				MAIN RUNNERS _ PROFILI PORTANTI			
code _ codice	type _ tipo			code _ codice	thickness _ spessore	colour _ colore	
ST090AA	strips pitch 90 mm open joint doghe passo 90 mm scuretto aperto			T 90/N	steel 0.6 acciaio 0.6	brown testa di moro	
	size dimensioni	incidence	incidenza		length lunghezza	incidence	incidenza
	84x16 mm	11 ml/mq			3600 mm	0.9 ml/mq	
						pcs_pz : 10	
ST090AN	strips corrugated pitch 90 mm open joint doghe ondulate passo 90 mm scuretto aperto			T 90/N	steel 0.6 acciaio 0.6	brown testa di moro	
	size dimensioni	incidence	incidenza		length lunghezza	incidence	incidenza
	84x16 mm	11 ml/mq			3600 mm	0.9 ml/mq	
						pcs_pz : 10	
				PC90	steel 0.6 acciaio 0.6	brown testa di moro	
					length lunghezza	incidence	incidenza
					3600 mm	variable variabile	
						pcs_pz : 10	
ST085AA	strips pitch 100 mm open joint doghe passo 100 mm scuretto aperto			T 85/N	steel 0.6 acciaio 0.6	brown testa di moro	
	size dimensioni	incidence	incidenza		length lunghezza	incidence	incidenza
	84x16 mm	10 ml/mq			4000 mm	0.9 ml/mq	
						pcs_pz : 10	
ST085AN	strips corrugated pitch 100 mm open joint doghe ondulate passo 100 mm scuretto aperto			T 85/N	steel 0.6 acciaio 0.6	brown testa di moro	
	size dimensioni	incidence	incidenza		length lunghezza	incidence	incidenza
	84x16 mm	10 ml/mq			4000 mm	0.9 ml/mq	
						pcs_pz : 10	
				PC90	steel 0.6 acciaio 0.6	brown testa di moro	
					length lunghezza	incidence	incidenza
					4000 mm	variable variabile	
						pcs_pz : 10	
ST150AA	strips pitch 150 mm open joint doghe passo 150 mm scuretto aperto			T150/N	steel 0.6 acciaio 0.6	brown testa di moro	
	size dimensioni	incidence	incidenza		length lunghezza	incidence	incidenza
	134x16 mm	6.67 ml/mq			4050 mm	0.9 ml/mq	
						pcs_pz : 10	

STRIPS / OPEN JOINT DOGHE / SCURETTO APERTO				MAIN RUNNERS _ PROFILI PORTANTI			
code _ codice	type _ tipo	code _ codice	thickness _ spessore	colour _ colore			
ST200AA	strips pitch 200 mm open joint doghe passo 200 mm scuretto aperto	T 85/N	steel 0.6 acciaio 0.6	brown testa di moro			
	size dimensioni	incidence incidenza				length lunghezza	incidence incidenza
	184x16 mm	5 ml/mq				4000 mm	0.9 ml/mq
						pcs_pz : 10	
ST018AA	joint gap for rounded strip open open joint scuretto interspazio per doga arrotondata, scuretto aperto						
	size dimensioni						
	18x16 mm						
ST100CC	strips pitch 100 mm closed joint doghe passo 100 mm scuretto chiuso	T200/Z	galvanized steel 0.6 acciaio zincato 0.6	galvanized zincato			
	size dimensioni	incidence incidenza				length lunghezza	incidence incidenza
	84x16 mm	10 ml/mq				4000 mm	0.9 ml/mq
						pcs_pz : 10	
ST100CN	strips corrugated pitch 100 mm closed joint doghe ondulate passo 100 mm scuretto chiuso	T 85/Z	steel 0.6 acciaio 0.6	brown testa di moro			
	size dimensioni	incidence incidenza				length lunghezza	incidence incidenza
	84x16 mm	10 ml/mq				4000 mm	0.9 ml/mq
						pcs_pz : 10	
ST150CC	strips pitch 150 mm closed joint doghe passo 150 mm scuretto chiuso	T150/Z	steel 0.6 acciaio 0.6	galvanized zincato			
	size dimensioni	incidence incidenza				length lunghezza	incidence incidenza
	134x16 mm	6.67 ml/mq				4050 mm	0.9 ml/mq
						pcs_pz : 10	
ST200CC	strips pitch 200 mm closed joint doghe passo 200 mm scuretto chiuso	T200/Z	galvanized steel 0.6 acciaio zincato 0.6	galvanized zincato			
	size dimensioni	incidence incidenza				length lunghezza	incidence incidenza
	184x16 mm	5 ml/mq				4000 mm	0.9 ml/mq
						pcs_pz : 10	

Finishing > cf. perforations / colours / acoustic inlay / perimetral moldings Finiture > vedi pagina perforature / colori / prestazioni acustiche / cornici perimetrali

PERFORATION


standard width < 600 mm

■ ● perforation

STANDARD PERFORATIONS


A

Ø 2.5 mm = 20% - parallel pitch 5 mm




B

Ø 2.5 mm = 7% - diagonal pitch 8.5 mm




C

Ø 2.0 mm = 6% - diagonal pitch 8 mm




D

Ø 2.0 mm = 12% - parallel pitch 7.5 mm




E - AP3

Ø 2.0 mm = 25% - diagonal pitch 3.5 mm




F - AP4

Ø 2.0 mm = 12.5% - parallel pitch 5 mm




G - APQ2

2 x 2 = 4.5% - parallel pitch 9.5 mm



H MICRO PERFORATION - AP0/1


Ø 0.7 mm - parallel pitch 5 mm




PERIMETRAL MOLDING

standard length 3000 mm


For special dimension perimetral moldings are available




20 X 24
CP10 aluminum 0.5/0.6 mm
A3000 steel 0.5/0.6 mm




24 X 40
CP20 aluminum 0.5/0.6 mm
A3002 steel 0.5/0.6 mm




24 X 24
CP11 aluminum 0.5/0.6 mm
A3001 steel 0.5/0.6 mm




19 X 31
CP30 aluminum 0.5/0.6 mm
A3003 steel 0.5/0.6 mm




24 X 20 X 20 X 24
CW2020 aluminum 0.5/0.6 mm
W3003 steel 0.5/0.6 mm



24 X 15 X 15 X 24
CW1515 aluminum 0.5/0.6 mm
W3004 steel 0.5/0.6 mm



20 X 12 X 12 X 24
CW1210 aluminum 0.5/0.6 mm
W3000 steel 0.5/0.6 mm



25 X 8 X 15 X 15
CW0815 aluminum 0.5/0.6 mm
W3002 steel 0.5/0.6 mm

COLOURS RANGE

STEEL / ALUMINIUM




white



RAL 9006
silver



RAL 7024
dark grey



RAL 9005
black



satin-finish aluminium

POWDER COATED



ALL RAL COLOURS

WOOD



SL57
whitened oak




SL56
cherry tree



SL252
winchester



SL02
light oak



SL302
dark oak



SL55
wenge

ALUMINIUM / MAT



RAL 1015
ivory



RAL 1001
beige



RAL 1021
cadmio yellow



RAL 1007
chrome yellow



RAL 2004
orange



RAL 3002
carmine red



navy blue



RAL 5017
blue



RAL 6018
pea green



RAL 6029
mint colour



RAL 8014
brown

ALUMINIUM / BRIGHT



aisi steel
310



brass yellow
330



gold
260

The range of colours shown on this page is purely indicative, and we recommended that you request the samples. For other colours, please ask about the availability in stock.

For further details, refer to the bundle of RAL colours and CBI's exclusive colours bundle, or contact the technical department at CBI Europe.

LINEAR STRIPS: design and functionality, 100% made in Italy.

CBI Europe's Linear Strips suspended ceiling system is the perfect solution for civil and industrial buildings. These highly functional architectural elements combine thermal and acoustic insulation with the ability

to integrate ventilation, lighting and security systems. The fully inspectable strips come in various modular types and designs to allow the suspended ceiling to adapt to all spaces and layouts.



AESTETICH VERSATILITY



LIMITLESS CONFIGURATION



HI-TECH PERFORMANCES

Why

VERSATILE, FUNCTIONAL, LONG LASTING AND EASY TO INSTALL: A PERFECT COMBINATION OF TECHNOLOGY AND DESIGN THAT GUARANTEES HYGIENE AND STRENGTH.

Where

LARGE PUBLIC SPACES - HALLS, SHOPPING CENTRES, AIRPORTS, BANKS, OFFICES, CORRIDORS, STERILE ENVIRONMENTS, THEATRES, CANTEENS, HOSPITALS - OUTDOORS AND INDOORS.

Benefit

- **ACHIEVING FLEXIBLE, COMFORTABLE, CONTEMPORARY AND RESPONSIBLE INTERIORS.**
- **OBTAINING POINTS FOR LEED CERTIFICATION.**
- **SOUNDPROOFED ENVIRONMENTS.**
- **SPEEDING UP CONSTRUCTION.**
- **CONTAINING COSTS OF LABOUR AND MAINTENANCE.**
- **STRUCTURES 100% INSPECTABLE.**
- **INTEGRATION WITH ADVANCED CLIMATE CONTROL, DOMOTICS AND LIGHTING.**
- **PRECISE BUDGETING.**



FIRE REACTION

Including versions incorporating sound-absorbing non-woven fabric, are non-flammable according to the Italian Ministerial Decree of the 15th march 2005, and therefore conform to Euroclass A1 fire reaction requirements (only for not perforated panels).



HYGIENE

Easy to wash and sterilise. On request, they can also be supplied in a special fungicidal and bactericidal paint finish. We recommend hermetically sealed, Down Clip 200 System Metal Ceilings for use in operating theatres and pharmaceutical industries. All other types of metal suspended ceilings are ideal for use in kitchens, canteens, hospitals and schools. They also provide valuable protection against dust in industries producing delicate electronic circuits. Tests carried out under ISO 22196 ensure the reduction of the microbial population > 95% after 24 hours.



HUMIDITY RESISTANCE

Maintain their dimensional stability even under extreme ambient conditions, and can therefore be installed in environments characterised by high levels of relative humidity and large variations in temperature. For outdoor installations, please contact CBI Europe's Technical Department.



PAINTWORK

Suspended ceilings in pre-painted aluminium and hot-galvanised and pre-painted FePO2 steel are coil-coated with primer and polyester paint to a thickness of 25 microns. Suspended ceilings in electro-galvanised and post-painted FePO2 steel are electrostatically coated with resin based, thermosetting, polyester powder paints to a thickness of 60 microns.



LIGHT REFLECTANCE

All metal suspended ceilings finished in white and unperforated > 85% have a standard gloss level of 20.



INTEGRATED ACCESSORIES

All metal suspended ceilings can be fitted with accessories such as lighting units, ventilation vents, smoke detectors, sprinklers and suspended signage



FASTNESS

The systems are designed to guarantee rapid installation, speeding up the installation phases and respecting all the requirements of planarity and orthogonality.



ACOUSTIC ABSORPTION

Ceilings and coverings combine acoustic performance, comfort and aesthetics with adequate absorption values. Upon request they can be supplied with certifications issued by independent companies.



LEED CERTIFICATION

All products are manufactured in certified and constantly monitored processes to guarantee the highest standards of quality and safety.



ANTI-SEISMIC

The systems guarantee the application of all good safety practices in the construction and development of dedicated projects. Upon request, they can be supplied with an anti-seismic reports, which indicate suitable bracing.